



PharmaSafe+'s Narcotics Safes & Cabinets were designed by a Pharmacist to fit into existing standard shelving fixture units & offer a highly visible physical deterrent to Burglary, Robbery, & Diversion crime. Our Narcotics Safes allow Pharmacists, Doctors, & other health professionals to incorporate a secure storage solution into your existing work flow and dispensing procedures. All narcotics and "high risk" drugs are securely placed into the heavy duty Narcotics Safes which remains locked at all times. When your staff needs access to the unit they can use a key, or their unique pass code or fingerprint to gain access. This process takes seconds. The Electronic Access Controllers we use were originally developed for the banking industry & have received custom programming for optimal use in pharmacies.

NARCOTIC SAFE DESCRIPTIONS & SPECIFICATIONS:

Standard dimensions are 12" deep x 77" tall x 36" wide & come with double doors. The units are constructed out of 11 gauge heavy duty steel. Have 5 standard adjustable shelves & one center shelf welded into place to add structural integrity & defend against crow bar or pry attacks. Units are inserted in place of existing shelving and must be bolted to the floor & / or wall. Units weight approximately 500LBS.

NC-1277K (STANDARD UNIT w/ High security key):

- 12"D x 36"W x 877"H (hinge extends out approximately 1 inch beyond spec dimensions)
- Total Weight: 457 LBS *(all weights are approximate & may vary)

Standard Features Of Protector Series Narcotics Safes

- Heavy duty 11 gauge steel plate construction
- Durable & easily sanitized smooth white finish
- Double door overlay with anti-pry guard wraps designed to defend against attacks
- Tamper Proof Hinges
- Recessed Doors to avoid pry
- Basic Key operated Lock & Latch
- High security locking system with 3/4" diameter boltwork
- (3) 3/4" diameter high security jamb bolts on each door jamb
- Tamper proof safe hinges and 3/4" diameter bolt work
- Pre-punched holes to securely and permanently bolt to floor
- Reinforced 11 gauge all welded construction
- Adjustable & flexible Shelving system allows for maximum storage capacity
- (5) standard adjustable shelves & (1) welded in place center shelf included
- Accommodates up to a total of (13) adjustable pharmacy style shelves
- Prominent oversized warning labels deter robbery, burglary and internal diversion
- Available installation and set-up by a certified technician

****Custom cabinet sizes & configurations available upon request****

ELECTRONIC ACCESS CONTROLLERS

We feature two Electronic Access Controller options for our Narcotics Safes. Each of the Electronic Access Controller options allow an administrator or manager to set up users, time delay opening (NOT MANDATORY), open periods, user audit trail reporting, duress / panic silent alarms (must be wired into your existing alarm system), & software to manage & store user access audit reporting. The main differences in the controllers generally are (more specific specifications below):

PROTECTOR PLUS SERIES



66E- Electronic Access Controller & locking mechanism (Keypad w/ pin code entry)

- allows for 9 users including one manager & one administrator
- Unit supports an audit trail by logging & recording the last 512 user events
- User Audit report show only User location numbers 01 through 09 in reporting & audit forms (administrator must keep track of Users & their locations)
- Unit uses pin code entry only
- Unit uses high quality 9 volt alkaline battery power (powers 1yr)
- Optional time delay opening function
- Integrated panic/duress silent alarm function (must be connected to existing site Alarm System)
- Simply & quickly set-up all users and user access rights

PROTECTOR ELITE SERIES



2. SmartPoint- Electronic Access Controller (Biometric Fingerprint authentication with Pin Code)

- Allows for 99 users including one manager & one administrator
- Unit supports an audit trail by logging & recording the last 1,000 user events
- User Audits show users names in reporting & audit forms
- Unit can be set up to use biometric only, biometric w/ pin code, pin code only
- Unit requires AC power supply
- Integrated panic/duress silent alarm function (must be connected to existing site Alarm System)
- Simply & quickly set-up all users and user access rights

TECHNICAL ELECTRONIC ACCESS CONTROLLER SPECIFICATIONS:

PROTECTOR PLUS SERIES

66E - Electronic Access Controller

AuditGard 66E Firmware

Product Features

Angular Round Entry (Audit & E-Key) Satin Chrome

- Manager Mode
- External Connection for Audit Trail
- Optional Audit Interface Required
- Internal Bolt Switch
- User Status Signal
- Wrong Try Penalty
- Signal to Disable Lock Opening
- Optional Alarm Box Required
- UL, EN 1300, VdS, DNV Certified
- Time Delay - Key Pad or PC Programmable
- Delay Period: 1-99 Minutes
- Open Period: 1-19 Minutes
- External Emergency Power Terminals PC Programmable Features
- Multiple Users - Up to 9
- 1 Manager and 8 Users
- Time Delay Override (User 9)
- Silent Signal Alarm - Optional Alarm Box Required
- Signal to Disable All Lock Functions
- Optional Alarm Box Required
- Dual Token (Factory Programming Required)
- E Key or E Key II

Features and Benefits

Users

Controller, One Manager and Eight Access Users

Audit Trail

Utilizing LG View Software, the last 512 events are captured with date and time stamp.

Time Delay

Entering a valid combination will begin the delay period. The lock can not be opened until the delay period ends.

Delay Period: 1-99 minutes

Open Period: 1-19 minutes

Time Delay Override Mode

Enables User 9 to override the delay period.

Dual Code

Requires the use of two valid combinations to open the lock

Dual Token

Use of either the eKey or eKey II along with user code for identification purposes.

Silent Alarm

(Alarm box 2789 or 4002 required.) Duress signal is sent to alarm box if the last number of the combination is entered either using one number higher or lower. Lock will open without indication that duress signal has been sent to the alarm system.

Remote Override Signal/Signal to Disable Lock

(Alarm box 2789 or 4002 required) Input signal to the Alarm Box will disable opening of the lock by a valid combination or disable all lock functions.

Wrong Try Penalty

Four consecutive invalid codes initiates five minute delay period.

Low Battery Signal

Lock Types Available

4300M Swing Bolt Lock

6040M Dead Bolt Lock

6441 Redundant Mechanical

4-Wheel Lock

Certifications

UL Listing, Type 1

VdS Listing, Class 2

PROTECTOR ELITE SERIES

SMARTPOINT BIOMETRIC Electronic Access Controller

Benefits of Biometrics

- Increase management efficiency for the control of employee safe access rights.
- Eliminate hard and soft costs associated with keys and combinations.
- Create a non-refutable identification and hold each user accountable through extensive audit capabilities.
- Control multiple compartments within a single safe with one biometric unit.
- Economical retrofit for existing mechanical or electronic locks.
- Biometric reader passed the Class 1 requirements set forth by the U.S. National Biometrics Security Project

(NBSP) with a false acceptance rate of less than one in one million.

Biometric Features

Light Emitting Sensor Technology

Highest usability

- Curved face
- Teflon contact surface
- Highest quality image generation (650 DPI captured)

Durability

- No Electro Static (ESD) sensitivity
- Does not absorb skin oils or nicotine
- Tested to 1.5 million touches
- Designed for high traffic applications

Intrinsic Live Finger Sensing

- No False Reject Rate (FRR) impact
- Spoof-proof - cannot be fooled with artificial gummy or silicon replicas

Specifications

Environment

Temperature - 32°F to 120°F (0°C to 49°C) Humidity - 86°F (30°C) and 85% relative humidity for 24 hours

Verification Time

Less than 1 second, typical

Maximum # Templates: 100

- 100 users/1 fingerprint per user
- 50 users/2 fingerprints per user
- 33 users/3 fingerprints per user

Power

Recommended 12v DC (regulated) Maximum 14v DC 9v battery backup in the event of power failure

Communication

RS-485. Minimum 9.6k baud, maximum 38.4k baud.

Memory

Non-volatile. Information contained in lock (including logs and set-up) will not be lost in the event of power loss.

Input (logic) module: Zamak**Keypad**

Highly durable polyester with domed keys.

LCD Display

Back-lit for viewing ease.

Stored Audit Events

- Lock 4000
- Logic Module 1000

Time Lock

Two time lock periods are available and selectable by lock.

Time Delay

Entering a valid combination will begin the delay period. The lock can not be opened until the delay period ends.

Delay Period: 1 - 99 minutes • Open Period: 1 - 19 minutes

Time Delay Override

Enables any user assigned for this feature to override the delay period and open the lock.

Dual Code

Requires the use of two valid combinations (and/or fingerprints with biometrics) to open the lock.

Silent Alarm

Duress signal is sent to alarm box if the last number of the combination is entered using either one number higher or lower.

Lock will open without indication that duress signal has been sent to the alarm system.

Remote Override

Input signal to the Alarm Box will disable opening of the lock by a valid combination (or finger with biometrics).

Multiple System Operation Modes (SmartLinc II /SmartPoint)

- Code Only†
- Dual Code†
- Finger Only*
- Finger plus Code*†
- 2 Fingers*
- 2 Fingers plus 2 Codes

